

# TOP LINE

## 3A Plug Valves



Stainless Steel

Flow Control

Equipment for the

Food and Beverage,

Dairy, Cosmetics,

Biotechnology,

Pharmaceutical and

Electronics Processing


Industries

### FEATURES

- Rubber (Buna) or Stainless Steel Plug
- Materials Type 304 Stainless Steel
- 3A Sanitary Finish • Temperature to 100° F
- Bevel Seat Ends available on request
- 316 Stainless Steel available on request


Plug valves are excellent sanitary devices with minimal pressure drops. The TOP FLO® Plug Valve features a tapered core assembly which allows easy cleaning while eliminating crevices which can lead to contamination.

These valves are constructed with a special taper which has been carefully designed to reduce wedging and galling. These rugged valves are made of type 304 or 316L stainless steel and come in Clamp or Butt-Weld end connections. Other connections available upon request. Available in rubber or steel plugs.




#### D10WW 2-WAY PLUG VALVE BUTT-WELD

Size (Tube O.D.)	A	B	C	D	E	Stock No. Stainless Steel Plug	Stock No. Rubber Plug
1	3-5/8	7-1/4	5-1/16	4-39/64	2-19/64	359610	359610R
1-1/2	2-29/32	7-13/16	6-7/16	5-5/8	2-13/32	359615	359615R
2	4-13/32	8-13/16	7-1/64	5-43/64	2-27/32	359620	359620R
2-1/2	5-1/8	10-1/4	8-51/64	5-59/64	3-25/64	359625	359625R
3	5-23/32	11-7/16	9-1/2	7-1/8	3-9/16	359630	359630R




#### D11WWW 3-WAY PLUG VALVE BUTT-WELD

Size (Tube O.D.)	A	B	C	D	E	Stock No. Stainless Steel Plug	Stock No. Rubber Plug
1	3-5/8	7-1/4	5-1/16	4-39/64	2-19/64	359710	359710R
1-1/2	2-29/32	7-13/16	6-7/16	5-5/8	2-13/32	359715	359715R
2	4-13/32	8-13/16	7-1/16	5-43/64	2 27/32	359720	359720R
2-1/2	5-1/8	10-1/4	8-51/64	5-59/64	3 25/64	359725	359725R
3	5-23/32	11-7/16	9-1/2	7 1/8	3 9/16	359730	359730R



#### D10MP 2-WAY PLUG VALVE CLAMP

Size (Tube O.D.)	A	B	C	D	E	Stock No. Stainless Steel Plug	Stock No. Rubber Plug
1	2-9/16	4-9/16	5-1/16	4-39/64	2-19/64	329610	329610R
1-1/2	2-29/32	5-13/16	6-7/16	5-5/8	2-13/32	329615	329615R
2	3-13/32	6-13/16	7-1/16	5-43/64	2-27/32	329620	329620R
2-1/2	4-1/8	8-1/4	8-51/64	5-59/64	3-25/64	329625	329625R
3	4-23/32	9-7/16	9-1/2	7-7/8	3-9/16	329630	329630R



#### D11MP 3-WAY PLUG VALVE CLAMP

Size (Tube O.D.)	A	B	C	D	E	Stock No. Stainless Steel Plug	Stock No. Rubber Plug
1	2-9/16	4-9/16	5-1/16	4-39/64	2-19/64	329710	329710R
1-1/2	2-29/32	5-13/16	6-7/16	5-5/8	2-13/32	329715	329715R
2	3-13/32	6-13/16	7-1/16	5-43/64	2-27/32	329720	329720R
2-1/2	4-1/8	8-1/4	8-51/64	5-59/64	3-25/64	329725	329725R
3	4-23/32	9-7/16	9-1/2	7-7/8	3-9/16	329730	329730R

**Note:** Plug Valves, because of their inherent design, are recommended only for low pressure applications ... 25 psi maximum; for use with non-hazardous products, and at temperatures not to exceed 100°F. They are subject to leakage almost from the initial time of installation because of normal operating, maintenance, and cleaning procedures. CAUTION: Butt-Weld End dimension is minimum center to face length and will require skillful welding techniques and proper cooling of valve body to prevent warpage.

## CONTACT YOUR TOP LINE SALES REPRESENTATIVE FOR ASSISTANCE

**Office:** P.O. Box 264  
Bradford, PA 16701

**Plant:** 21 Valley Hunt Drive  
Lewis Run, PA 16738

**TOP LINE**  
PROCESS EQUIPMENT COMPANY

**Phone:** 800-458-6095  
814-362-4626

**FAX:** 814-362-4453

