

PORTABLE HYDRAULIC POWER UNIT

MODEL HT35DD

This power unit is driven by a Deutz air cooled diesel engine and is designed to drive several of our pump models including the S4VHL. A large, built-in fuel tank allows this unit to run up to 24 hours between refills. Other equipment that require flows to 20 GPM may also operate from this power unit.



FEATURES


- Highway Trailer Chassis with Built-In Fuel Tank and Independent Suspension
- Single Point Lifting Bracket
- Automatic Engine Safety Shutdown Package
- Vane-Type Hydraulic Pump
- Spin-On Return Filter W/ Indicator
- Variable Speed Control
- Tank Top Filler/ Strainer
- System Relief Valve
- Pressure Control Valve
- Liquid Filled Pressure Gauge
- Fluid Level/ Temperature Gauge

OPTIONS:

- Skid Frame
- Multiple Hydraulic Circuits
- Other Flow and Pressure Combinations

A0100

Model HT35DD Overall Dimensions



SPECIFICATIONS

ENGINE:..... Deutz F3L1011F Air Cooled Diesel
HORSEPOWER:..... 35 @ 2300 RPM
HYDRAULIC OUTPUT*:..... Variable, Max. 20 GPM (76 LPM)
OPERATING PRESSURE*:..... Maximum 2500 PSI (170 Bar)
HOSE PORT SIZE:..... 3/4" or 1" NPT
HYDRAULIC OIL:..... SAE 10W or 20W Type AW
..... also: Bio-degradeable oil (Consult Factory)
OIL FILTRATION:..... 10 Micron (Standard)
OIL RESERVOIR CAPACITY:..... 30 U.S. Gallons (114 Liters)
FUEL TANK CAPACITY:..... 40 U.S. Gallons (151 Liters)
FUEL CONSUMPTION:..... Approx. 1.7 U.S. Gal/Hr (6.4 Liters/Hr)
DIMENSIONS:..... H 60" (152 cm) x W 60" (152 cm) x L 108" (279 cm)
WEIGHT (Dry):..... 1580lbs. (716 kg)

* For Flows and Pressures Other Than Standard, Consult Factory

Since we are constantly working to improve our products, specifications are subject to change without notice.



P.O. Box 537, Mt. Holly, NJ 08060, USA Phone: 609-267-5393 FAX: 609-261-8070
Website: www.hydra-tech.com E-Mail: htpump@hydra-tech.com